

PP 850 Kompact u containeru (Švedski proizvod)

Technical data

Postrojenje je namjenjeno za prešanje piljevine i druge biomase vlažnosti do 15 %.

| Machinetype | 850 kg/h |
|-------------------------------------|-----------------|
| Fan suction apparatus | 2,2 kW |
| Main engine 400V 3-fas | 75 kW |
| Cooling fan | 4 kW |
| Engine for the scissors 400V 3-fas | 1,1 kW |
| Engine for feeder 400 V 3-fas | 1,1 kW |
| Rotary valve 400V 3-fas | 0,37 kW |
| Oil pump 400V 3-fas | 0,75 kW |
| Cooling fans 230V | 0,2 kW |
| Vibrating engine | 0,18 kW |
| Elevator | 0,55 kW |
| Engine mixer | 0,75 kw |
| TOTAL required power output: | 113,3 kW |

| Basedata | PP 850 |
|-------------------------------------|--------|
| Length Compact (cm) | 3 600 |
| Width Compact (cm) | 2 400 |
| Height Compact (cm) | 4 860 |
| Length Factory in Box exkl. cyclone | 6 060 |
| Width Factory in Box exkl. cyclone | 2 450 |
| Height Factory in Box exkl. cyclone | 2 600 |
| Height Factory in Box inkl. cyclone | 4 450 |
| Producing capacity, up to (kg/h)) | 1 000 |

